



Designer Cover  
Coming  
Soon!

## QUICK-CHANGE FILTRATION SYSTEMS

- Easy to install, easy filter change
- Unique cover for single unit for a more appealing look
- Reversible metal brackets for 1, 2 or 3 cartridges†
- 1/4-inch or 3/8-inch John Guest® push-fit connections available
- 1/4-inch compression connections available for flex hose connections
- Seven cartridge models to choose from to meet specific application needs

†The Twin and Triple systems are not performance tested or certified by NSF.

PENTEK® Quick Change Filtration Systems are designed for easy installation and cartridge change. 1/4-inch or 3/8-inch push fittings, as well as 1/4-inch compression fittings, on the inlet and outlet sides of the filter head allow effortless installation. Many single systems are NSF Certified.

The cartridge filter is easily changed with a quarter-turn of the filter. Water is automatically shut off during the change of the filter through the auto shut-off feature built into the filter head. This feature eliminates the need for additional shut-off valves to and from the filter system.

The PENTEK quick-change filter system offers several cartridge options to meet the demands of varying water conditions. The granular activated carbon cartridge offers extended chlorine taste and odor performance with low pressure drop.\* The EP carbon block filter offers superior chlorine taste and odor performance with 5 micron sediment reduction.\* The CBR carbon block cartridge has enhanced performance capabilities for chlorine taste & odor, cyst, lead, atrazine and lindane reduction.

The new cartridges include carbon/phosphate cartridge, chloramine reduction cartridge, sediment only

cartridge, a high performance 1-micron carbon block cartridge, and the soon to be released membrane filter cartridge for bacteria and virus reduction.\*

PENTEK's quick-change filter system applications include:

- under-sink drinking water
- refrigerator/icemaker
- pre/post RO membrane
- vending machine
- ice machine
- coffee machine
- other OEM applications

\* Not performance tested or certified by NSF.

\*Not Performance Tested or Certified by NSF.



**PENTEK**  
Pentair Water

# QUICK-CHANGE

## Filtration Systems



\*Shown with optional designer cover  
The Twin and Triple systems are Not Performance Tested or Certified by NSF.

Model	Cartridge Color	Claims	Filter Life	Flow Rate	Micron Rating	1/4-inch Threaded	1/4-inch JG Push fit	3/8-inch JG Push fit
QC10-CBR	White	chlorine taste & odor, sediment, lead, atrazine, lindane, cyst and turbidity	500 gallons (1890 L)	0.5 gpm (1.9 L/min)	0.5	•	•	•
QC10-EP	White	chlorine taste & odor	1,500 gallons (5670 L)	0.5 gpm (1.9 L/min)	5†	•	•	•
QC10-GAC	Blue	chlorine taste & odor	2,500 gallons (9460 L)	0.75 gpm (2.8 L/min)	–	•	•	•
QC10-TSGAC	Blue	chlorine taste & odor with phosphate crystals	1,700 gallons (6435 L)	0.75 gpm (2.8 L/min)	–	–	•	•
QC10-SED1	White	sediment	–	0.6 gpm (2.3 L/min)	1	–	•	•
QC10-CGAC†	Blue	chloramine taste & odor and chlorine taste & odor†	500 gal. (1890 L) chloramine* 10,000 gal. (37850 L) chlorine*	0.6 gpm (2.3 L/min)	–	–	•	•
QC10-CB1	White	chlorine taste & odor and sediment	10,000 gallons (37850 L)	0.6 gpm (2.3 L/min)	1	–	•	•

\*Filter life based on chlorine reduction as tested by Pentair Filtration, Inc.

†Not Performance Tested or Certified by NSF.



The QC10-CBR is Tested and Certified by NSF/ANSI to Standard 42 for the reduction of Chlorine Taste & Odor and Particulate Class I. Standard 53 Atrazine, Cyst, Lead, Lindane and Turbidity.



The QC10-SED1 is Tested and Certified by NSF International to NSF/ANSI Standard 42 for the aesthetic reduction of Particulate Class 1.



QC10-EP is Tested and Certified by NSF/ANSI to Standard 42 for the reduction of Chlorine Taste & Odor.



The QC10-CB1 is Tested and Certified by NSF International to NSF/ANSI Standard 42 for the aesthetic reduction of Chlorine Taste & Odor and Particulate Class 1.



QC10-GAC and QC10-TSGAC is Tested and Certified by NSF/ANSI to Standard 42 for the reduction of Chlorine Taste & Odor.

**WARNING:** Do not

**CAUTION:** Protect against freezing to prevent cracking of the filter housing and water leakage.

Note: Cartridge will contain a very small amount of carbon fines (a very fine black powder). After installation and before using the water follow the instructions for flushing the cartridge to remove fines.

U.S. Patent Numbers 5,976,432 and 5,823,668



502 Indiana Avenue • P.O. Box 1047 • Sheboygan, Wisconsin 53082-1047  
Customer Service: 800.645.0267 • Fax: 888.203.7361 • supportspecialist@pentekfiltration.com  
International: 920.457.9435 • Fax: 920.457.2417 • international@pentekfiltration.com  
www.pentekfiltration.com

©2006 Pentair Filtration, Inc.

Printed in USA AU06 310125