

Spec Sheet

1042LH (GFI #5144)	
Type	Flow-Through Humidifier
GPD (Based on 120° Plenum Temperature)	17
Dimensions (Inches)	14 H x 15.125 W x 9 D
Weight (Pounds)	13
Replacement Vapor Pad® (Replace Once Each Season)	990-13 (GFI #7002)
Home Size (Sq. Ft.)	To 2,800
Installation	Warm Air / Return Air Plenum / Right of Left Side
Plenum Opening (Inches)	13.625 W X 9.5 H
Bypass Opening (Inches)	6
Pallet Qty.	30
Cabinet Construction	UV-Stable Automotive Grade Plastic
Humidistat	MHX3C
Voltage (Volts)	24
Warranty (Years)	5
In The Box	Humidifier, MXH3C Humidistat, Installation Instructions, Mounting Template, Vapor Pad®, Parts Kit With Push-to-Connect Valve, Transformer, Stainless Steel Distributor Tube, Damper, 15'-5/8" Drain Hose, Drain Pan, Solenoid Valve.



1042LH



MXH3C
 Manual Humidistat
 GFI #7038
 Included

Accessories



990-53
 Solenoid Valve
 GFI #7014



Designed & Assembled
 in Michigan, USA




Spec Sheet

Models 1042LH Features

- Model 1042LH is suitable for homes up to 2800 square feet.
- Cover is UV stable.
- Stainless steel distributor tube allows for either cold or hot water supply.
- MHX3C manual control humidistat is included.
- A long-standing model; considered the “work horse” of humidifiers.

Installation

Vertical plenum surface of any forced air furnace



Installation Options:

- Warm Air Plenum
- Return Air Plenum
- Right or Left Bypass
- Vertical or Horizontal
- Furnace or Air Handler

Installs Quickly & Easily

Maintenance

Change the Vapor Pad® at least once per year

Product Support

- Installation Manual
- Home Owner Brochure
- www.generalaire.com
 - Maintenance Video
 - Help Topics
 - Product Information
- Tech Support (866) 476-5101



990-13 Vapor Pad®
 (GFI #7002)