

Performance Data Sheet

Model: AP EASY - COMPLETE

These systems have been tested according to NSF/ANSI Standard 42 and Standard 53 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42 and Standard 53.



System tested and certified by NSF International against NSF/ANSI Standard 42 and Standard 53 for the reduction of substances as listed below according to Standard 42 and 53.

Capacity (750 Gallons) Contaminant Reduction Determined by NSF

Contaminant Reduction	Average Influent	NSF specified Influent Challenge Concentration	Avg. % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Test Report
Chlorine Taste and Odor	1.88	2.0 mg/L + 10%	97.3	0.06 mg/l	≥ 50%	511081-03
Lead at pH 6.5	0.153 mg/L	0.15 mg/L ±10%	99.3	0.001	0.010 mg/L	511072-03
Lead at pH 8.5	0.150 mg/L	0.15 mg/L ±10%	99.3	0.001	0.010 mg/L	511073-03
Benzene	0.014 mg/L	0.015 mg/L ±10%	92.1	0.005	0.005 mg/L	512951-03
P-Dichlorobenzene	0.210 mg/L	0.225 mg/L ±10%	99.8	0.005	0.075 mg/L	512953-03
Toxaphene	0.015 mg/L	0.015 mg/L ±10%	93.3	0.001	0.003 mg/L	511504-03
Particulate class I 0.5- <1um	5700000	10000/ml	99.40	30583	≥ 85%	511079-03
Cysts	166,500/L	Minimum 50,000/L	99.99	1	>99.95%	511077-03

Application Guidelines/Water Supply Parameters	
Service flow	0.78 gpm
Water supply	Community or private well
Water pressure	25 - 125 psi (172 - 862 kPa)
Water temperature	40° F - 100° F (4.4° C - 38° C)

It is essential that operation for the maintenance and filter replacement requirements be carried out product to perform as advertised. Note that while the testing was performed under standard laboratory conditions, actual performance may vary. Systems must be installed and operated in accordance with manufacturer's recommended procedures and guidelines. See Warranty card

Replacement Cartridge: AP EASY C-COMplete

3M is a trademark of 3M Company.
NSF is a trademark of NSF International.
© 2016 3M Company. All rights reserved.
34-8718-3863-6

⚠ WARNING

To reduce the risk associated with ingestion of contaminants:
 • Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

NOTICE

To reduce the risk associated with property damage due to water leakage or flooding:
 • Read and follow all Instructions before installation and use of this system.
 To reduce the risk of water leakage or flooding, and to ensure optimal filter performance:
 • Change the disposable filter cartridge every six months or sooner if you observe a noticeable reduction in water flow rate.
 • Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and cracks in the filter housing, causing water leakage or flooding.
 • For questions or concerns, please contact Customer Service at 1-800-243-6894.

Parts and service available from:



3M Purification Inc.
 400 Research Parkway
 Meriden, CT 06450 U.S.A
 Toll Free: 1-800-222-7880
 Worldwide: 203-237-5541
 Fax: 203-238-8701

www.aquapure.com • www.3Mpurification.com